

Up to 96% AFUE, TWO-STAGE, ECM GAS FURNACE

EASIER TO SELL

- Up to 96% AFUE, all models, all positions
- All models have earned the ENERGY STAR®
- Two-stage heating operation
- Xtra SEER ECM blower motor
- Supports single- and two-stage cooling units
- Approved for twinning applications (0601412 through 1202420) with accessory (order separately)
- Dehumidification feature in cooling
- Electronic air cleaner terminal
- California NOx approved
- Certified 2% or less leakage of nominal air conditioning CFM delivered when pressurized to 1-inch water column with all present air inlets, air outlets, and condensate drain port(s) sealed

TOUGHER

- Flame roll-out sensors standard
- Adjustable heating blower OFF delay
- Factory set blower ON delay
- Stainless steel secondary heat exchanger
- High temperature limit control prevents overheating
- Direct ignition with Silicon Nitride ignitor
- High-quality, corrosion-resistant, one-piece steel cabinet

QUIETER

- Operates at quieter, lower heating rates
- Two-speed induced draft combustion blower
- Insulated steel cabinet

EASIER TO INSTALL AND SERVICE

- Direct vent (2-pipe), single-pipe venting, or ventilated combustion air
- 24 VAC humidifier terminal
- 35" (889mm) high, for ease of installation
- Innovative knobs for easy door removal and secure attachment
- Factory shipped for natural gas, with propane gas conversion kits available
- Four position – upflow/downflow/horizontal (left/right) installation
- At least twelve different venting configurations
- Through the casing flue pipe for counterflow or horizontal applications with accessory (order separately)
- Concentric vent available
- Self diagnostics with super bright LED
- Slide out heat exchanger assembly and blower assembly

WARRANTY *

- 5 year No Hassle Replacement™ limited warranty
- Lifetime heat exchanger limited warranty with timely registration
- 5 year parts limited warranty
- With timely registration, an additional 5 year parts limited warranty


* For owner occupied, residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Illustrations and photographs are only representative. Some product models may vary.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.



UNIT PERFORMANCE DATA

Model Number	Heating Input (MBTUH)	Efficiency AFUE	Cooling Capacity CFM range @ .5 in. w.c. (125 Pa)	Operating Dimensions Height x Width x Depth inches (millimeters)	Shipping Weight lbs (kg)	Notes
G9MXT0401410A	40,000	96%	385-925	35 x 14-3/16 x 29-1/2 (889 x 361 x 750)	125 (56)	
G9MXT0401712A	40,000	96%	330-1085	35 x 17-1/2 x 29-1/2 (889 x 445 x 750)	135 (61)	
G9MXT0601412A	60,000	95.5%	620-1090	35 x 14-3/16 x 29-1/2 (889 x 361 x 750)	136 (62)	
G9MXT0601714A	60,000	96%	530-1505	35 x 17-1/2 x 29-1/2 (889 x 445 x 750)	146 (66)	
G9MXT0801716A	80,000	96%	920-1610	35 x 17-1/2 x 29-1/2 (889 x 445 x 750)	156 (70)	
G9MXT0802120A	80,000	96%	795-2015	35 x 21 x 29-1/2 (889 x 533 x 750)	161 (73)	
G9MXT1002120A	100,000	96%	1105-2110	35 x 21 x 29-1/2 (889 x 533 x 750)	171 (77)	
G9MXT1202422A	120,000	96%	1215-2055	35 x 24-1/2 x 29-1/2 (889 x 622 x 750)	195 (88)	